

CustomTECH®

FLOORING PREPARATION SYSTEMS



NEW!

TechLevel™ LITE

High Flow Lightweight
Self-Leveling Underlayment

TechLevel™ Lite is a self-leveling underlayment formulated with CustomLite® Technology. It is 40% lighter than other self-leveling underlayment, making it easier to pour and carry. Excellent for installations where weight is a concern.

- Lightweight, sustainable formula; superior handling and weight reduction
- Superior crack resistance formula reduces shrinkage and cracks



Scan this to learn more about TechLevel LITE!



A DIVISION OF
CUSTOM®
A QUIKRETE® COMPANY

TechLevel™ LITE

High Flow Lightweight Self-Leveling Underlayment

A high quality flowable hydraulic cement underlayment / self-leveling underlayment formulated with CustomLite® Technology, TechLevel Lite is 40% lighter than other self-leveling underlayment, making it easier to pour and carry. Weighing just 3 lbs. (1.36 kg) per square foot (.093 m²) at 1/2" (13 mm) thickness, it is 3 lbs. (1.36 kg) lighter than traditional underlayment and excellent for installations where weight is a concern. A 30 lb. (13.6 kg) bag covers the same area as a 50 lb. (22.68 kg) bag.

Suitable as an Underlayment for:

- Carpet
- Wood and parquet flooring
- Luxury Vinyl Tile/Planks (LVT/LVP)
- Vinyl composition flooring (VCT)
- Sheet vinyl and rubber flooring
- Laminated flooring
- Ceramic, mosaic, quarry or cement body tile Impervious porcelain and glass tile
- Cement-based precast terrazzo
- Natural stone tile
- Terrazzo

Suitable Substrates*:

- Absorbent and non-absorbent concrete
- Gypsum-based underlayment (meeting ASTM F2419)
- Exterior grade plywood and OSB / APA or CANPLY Group 1
- Flooring manufacturer's approved wood underlayment
- Existing ceramic tile
- Resilient flooring
- Embossed vinyl
- Cutback adhesive residue
- Primed cement terrazzo
- Approved and prepared moisture control membranes
- Properly prepared steel and aluminum

*Preparation and/or primers may be required to bond to any of these substrates

Benefits of Product in the Installation:

- Lightweight, sustainable formula; superior handling and weight reduction
- Apply from feather edge up to 2" (2.5 cm) in one pour
- Superior crack resistance formula reduces shrinkage and cracks
- Exceeds ASTM requirements for resilient floor covering installations
- Exceeds ANSI requirements for tile and natural stone installations
- CUSTOM® cement products allow free passage of moisture

Ordering Information

ITEM CODE	SIZE	PACKAGE
TLLW30T	30 lb (13.6 kg)	Bag

Coverage

Typical square foot coverage per 30 lb. bag (square meter per 13.6 Kg)

THICKNESS	SQUARE FEET	THICKNESS	SQUARE METER
1/8"	45	3.2 mm	4.1
1/4"	22.5	6.4 mm	2
1/2"	11.25	13 mm	1
1.0"	5.62	25 mm	0.52
2.0"	2.81	51 mm	0.26

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2024 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS220 4/24R



A DIVISION OF

CUSTOM®

A QUIKRETE® COMPANY