

# CustomTECH<sup>®</sup>

FLOORING PREPARATION SYSTEMS



**NEW!**  
10 lb.  
Bag

## SILK<sup>®</sup>

### Premium Patching & Finishing Compound

**SILK is a fast-curing, premium patching and finishing compound that provides a smooth finish to a variety of substrates prior to the installation of floor coverings.**

- Superior mixing and handling
- Excellent for skim coat patching applications
- No additives required
- Apply from featheredge to 1" (2.5 cm)
- Install flooring in as little as 15 minutes



Scan this to learn more about SILK!



A DIVISION OF  
**CUSTOM<sup>®</sup>**  
A QUIKRETE<sup>®</sup> COMPANY

# SILK®

## Premium Patching & Finishing Compound

A fast-curing, premium patching and finishing compound that provides a smooth finish to a variety of substrates prior to the installation of floor coverings. Formulated with Controlled Cure Technology™, SILK helps eliminate installation problems of bond failure, crumbling, mildew and staining of resilient flooring due to free-moisture found in traditional underlayment. Its rapid setting formula allows installation of most floor coverings in as little as 15 minutes.

### Suitable as an Underlayment for:

- Luxury Vinyl Tile (LVT)
- Luxury Vinyl Planks (LVP)
- Carpet flooring
- Vinyl Composition Tile (VCT)
- Sheet vinyl flooring
- Rubber flooring
- Hardwood; laminate and parquet flooring
- Porcelain, ceramic, glass, natural stone and terrazzo

### Suitable Substrates\*:

- Concrete, masonry and terrazzo
- Gypsum-based underlayment
- Existing resilient flooring
- Cutback adhesive residue
- Approved plywood and OSB
- Moisture mitigation membranes
- Existing ceramic tile and CBU

\*Preparation and/or primers may be required to bond to any of these substrates

### Benefits of Product in the Installation:

- Quick-setting formula permits floor covering installation in as little as 15 minutes
- Smooths the finishes on interior subfloors
- Patches and levels concrete and plywood from featheredge to 1" (2.5 cm)
- No additives required
- Compressive strength greater than 3000 psi

### Ordering Information

ITEM CODE	SIZE	PACKAGE
SILK10BT	10 lb (4.5 kg)	Bag

### Coverage

Typical square foot coverage per 10 lb. Bag (square meter per 4.5 Kg)

THICKNESS	SQUARE FEET		THICKNESS	SQUARE METER	
	MINIMUM	MAXIMUM		MINIMUM	MAXIMUM
SKIM COAT	100	300	SKIM COAT	9	27
1/8"	33.3	35.9	3.2 mm	3	3.3
1/4"	16.6	17.9	6.4 mm	1.5	1.6
1/2"	8.3	8.9	13 mm	0.7	0.8
1.0"	4.1	4.4	25 mm	0.3	0.4

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at [CustomBuildingProducts.com](http://CustomBuildingProducts.com) or contact CUSTOM Technical Services at 800-282-8786.



**Warranty:** Flooring Installation Systems products are backed by up-to a 25-year warranty. See [CustomTechFlooring.com](http://CustomTechFlooring.com) for full warranty information including limitations and exclusions.

©2024 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit [customtechflooring.com](http://customtechflooring.com) for updated technical data sheets and SDS information.

Custom Building Products  
800-272-8786  
[CustomTechFlooring.com](http://CustomTechFlooring.com)  
SS193 4/24R



A DIVISION OF

**CUSTOM®**

A QUIKRETE® COMPANY