

# Custom**TECH**<sup>®</sup>

FLOORING PREPARATION SYSTEMS



## TechPrime<sup>™</sup> A

Advanced Acrylic  
Multi-Surface Primer

**TechPrime<sup>™</sup> A is an advanced acrylic primer and sealer that prepares surfaces for the application of an appropriate CustomTech<sup>®</sup> self-leveling underlayment.**

- Prepares surfaces for application of self-leveling underlayments
- For use over porous and non-porous surfaces
- Solvent-free



Scan this to  
learn more about  
TechPrime A!



A DIVISION OF

**CUSTOM<sup>®</sup>**

A QUIKRETE<sup>®</sup> COMPANY

# TechPrime™ A

## Advanced Acrylic Multi-Surface Primer

TechPrime™ A is an advanced acrylic primer and sealer that prepares surfaces for the application of an appropriate CustomTech® self-leveling underlayment. It seals porous and non-porous surfaces and improves the bond of the underlayment to the subsurface.

### Suitable Substrates:

- Absorbent concrete
- Non-absorbent concrete
- Lightweight concrete
- Existing ceramic tile
- Cement terrazzo
- Exterior grade plywood
- OSB
- Cutback adhesive residue
- VCT
- Approved moisture control membranes

### Benefits of Product in the Installation:

- Prepares Surface for Application of Self-Leveling Underlayments
- Use on porous and non-porous substrates; one product for all your primer needs
- Can be used over epoxy-based moisture vapor control products
- Single component — no mixing required
- High solids content enables exceptional bond strengths
- Easy to apply with broom or roller
- Solvent Free; VOC and SCQAMD Compliant

### Ordering Information

ITEM CODE	SIZE	PACKAGE
TECHAT1-2	1 gal (3.78 L)	Bottle
TECHAT	3.5 gal (13.25 L)	Pail

### Coverage

Typical square foot coverage per gallon (square meter per 3.78 L)

UNIT SIZE	DILUTION	MINIMUM COVERAGE	MAXIMUM COVERAGE
Non-Porous	Undiluted	400 sq ft (37.16 m <sup>2</sup> )	600 sq ft (55.74 m <sup>2</sup> )
Porous	1:3 (primer:water)	600 sq ft (55.74 m <sup>2</sup> )	1200 sq ft (111.48 m <sup>2</sup> )

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at [CustomBuildingProducts.com](http://CustomBuildingProducts.com) or contact CUSTOM Technical Services at 800-282-8786.



**Warranty:** Flooring Installation Systems products are backed by up-to a 25-year warranty. See [CustomTechFlooring.com](http://CustomTechFlooring.com) for full warranty information including limitations and exclusions.

©2025 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit [customtechflooring.com](http://customtechflooring.com) for updated technical data sheets and SDS information.

Custom Building Products  
800-272-8786  
[CustomTechFlooring.com](http://CustomTechFlooring.com)  
SS199 2/25R



A DIVISION OF

**CUSTOM**®

A QUIKRETE® COMPANY