

NORTH AMERICA'S #1 GROUT



POLYBLEND® PLUS! The grout you love *plus*

- ✦ Brighter, More Vivid Finished Color
- ✦ Enhanced Color Consistency
- ✦ Better Resistance to Efflorescence
- ✦ Meets ANSI A118.7*



Scan this to
learn more about
Polyblend Plus!



CUSTOM®

TILE INSTALLATION SYSTEMS

Polyblend® Plus Sanded Grout

Suitable Uses:

- Use to fill joint widths 1/8" to 1/2" (3.2 to 12.7 mm)
- May be used for both floor and wall installations
- Interior and exterior applications
- Residential and commercial applications
- Countertops, tub surrounds, showers and high traffic areas
- Submerged conditions (swimming pools, spas, water features and fountains)

Suitable Substrates:

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, mosaic, quarry, cement body tiles
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile

Standards

*Polyblend® Plus Sanded Grout exceeds ANSI A118.6 & meets ANSI A118.7 standards

Available Sizes

- 1 lb (.45 kg) tub
- 7 lb (3.17 kg) box
- 25 lb (11.34 kg) bag

Coverage

Square Feet per 25 lb. / m² per 11.34 kg

TILE SIZE	JOINT WIDTH				
	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6.4 mm)	3/8" (9.5 mm)	1/2" (12.7 mm)
1" x 1" x 1/4"	54	40	33	27	24
25 x 25 x 6.4 mm	5.0	3.7	3.1	2.5	2.2
4-1/4" x 4-1/4" x 1/4"	192	131	101	71	56
108 x 108 x 6.4 mm	17.8	12.2	9.4	6.6	5.2
12" x 12" x 3/8"	348	234	177	121	92
305 x 305 x 9.5 mm	32.3	21.7	16.5	11.2	8.6
18" x 18" x 3/8"	518	348	262	177	135
457 x 457 x 9.5 mm	48.1	32.3	24.4	16.5	12.5
6" x 24" x 3/8"	279	189	143	98	75
152 x 610 x 9.5 mm	26.0	17.5	13.3	9.1	7.0
12" x 24" x 3/8"	461	310	234	158	121
305 x 610 x 9.5 mm	42.8	28.8	21.7	14.7	11.2

Charts for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Product specifications are subject to change. Visit our website for the most updated information.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

©2023 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Polyblend® Plus Non-Sanded Grout

Suitable Uses:

- Use to fill joint widths up to 1/8" (3.2 mm)
- May be used for both floor and wall installations
- Interior and exterior applications
- Residential and commercial applications
- Countertops, tub surrounds, showers and high traffic areas
- Submerged conditions (swimming pools, spas, water features and fountains)

Suitable Substrates:

- Vitreous, semi-vitreous or non-vitreous tile
- Impervious porcelain and glass tile
- Cement-based precast terrazzo
- Natural stone tile

Standards

*Polyblend® Plus Non-Sanded Grout exceeds ANSI A118.6 standards

Available Sizes

- 1 lb (.45 kg) tub
- 10 lb (4.5 kg) box
- 25 lb (11.34 kg) bag

Coverage

Square Feet per 10 lb. / m² per 4.5 kg

TILE SIZE	JOINT WIDTH	
	1/16" (1.6 mm)	1/8" (3.2 mm)
1" x 1" x 1/4"	40	23
25 x 25 x 6.4 mm	3.7	2.1
4-1/4" x 4-1/4" x 1/4"	156	80
108 x 108 x 6.4 mm	14.5	7.5
12" x 12" x 3/8"	289	146
305 x 305 x 9.5 mm	26.8	13.6
18" x 18" x 3/8"	432	217
457 x 457 x 9.5 mm	40.1	20.2
6" x 24" x 3/8"	232	117
152 x 610 x 9.5 mm	21.5	10.9
12" x 24" x 3/8"	384	194
305 x 610 x 9.5 mm	35.7	18.0

DOWNLOAD CUSTOM'S MOBILE APP



Custom Building Products
800-272-8786
custombuildingproducts.com

SS202 11/23R